

BENDY PACKER

PRODUCT DESCRIPTION

BurrowTech Bendy Packers are products that allow point repair of bends in pipes. These are produced by vulcanizing SBR+NR rubber and high-strength fabrics. It is resistant to temperatures between -30°C and +70°C. The biggest advantage is that it allows repairs to be made in these areas by turning from 30°, 45° and 90° bends.

*Can be produced as a Push Rod compatible head.



Connection Type



Back Hook Design



Patch Length Stripes



Push Rod Connection



Push Rod Connection

BENDY PACKER

Product Code	Size Usage Range		Max. Working Pressure	Deflated Plug Dimensions			Approx. Weight
	Min. Diameter	Max. Diameter		Diameter	Length	Total Length	
	mm	mm	bar / psi	mm	mm	mm	kg
DP10012	100		2.0 / 29	43	1200	1550	1.5
DP10015	100		2.0 / 29	43	1500	1850	1.7
DP10020	100		2.0 / 29	43	2000	2350	2.2
DP10030	100		2.0 / 29	43	3000	3350	3.4
DP10040	100		2.0 / 29	43	4000	4350	4.5
DP10050	100		2.0 / 29	43	5000	5350	5.6
DP10012512	100	125	2.0 / 29	64	1200	1550	1.9
DP10012515	100	125	2.0 / 29	64	1500	1850	2.2
DP10012520	100	125	2.0 / 29	64	2000	2350	2.9
DP10012530	100	125	2.0 / 29	64	3000	3350	4.4
DP10012540	100	125	2.0 / 29	64	4000	4350	5.8
DP10012550	100	125	2.0 / 29	64	5000	5350	7.3
DP15012	150		2.0 / 29	71	1200	1550	2.3
DP15015	150		2.0 / 29	71	1500	1850	2.9
DP15020	150		2.0 / 29	71	2000	2350	3.8
DP15030	150		2.0 / 29	71	3000	3350	5.8
DP15040	150		2.0 / 29	71	4000	4350	7.7
DP15050	150		2.0 / 29	71	5000	5350	9.7
DP15017012	150	170	2.0 / 29	112	1200	1550	3.2
DP15017015	150	170	2.0 / 29	112	1500	1850	4.0
DP15017020	150	170	2.0 / 29	112	2000	2350	5.3
DP15017030	150	170	2.0 / 29	112	3000	3350	8.0
DP15017040	150	170	2.0 / 29	112	4000	4350	10.7
DP15017050	150	170	2.0 / 29	112	5000	5350	13.3
DP20022515	200	225	2.0 / 29	150	1500	1850	4.7
DP20022520	200	225	2.0 / 29	150	2000	2350	7.0
DP20022530	200	225	2.0 / 29	150	3000	3350	8.8
DP20022540	200	225	2.0 / 29	150	4000	4350	10.6
DP30015	300		1.5 / 22	214	1500	1850	6.5
DP30020	300		1.5 / 22	214	2000	2350	8.8
DP30030	300		1.5 / 22	214	3000	3350	10.6
DP30040	300		1.5 / 22	214	4000	4350	12.4
DP30050	300		1.5 / 22	214	5000	5350	14.1
DP40015	400		1.5 / 22	290	1500	1850	9.1
DP40020	400		1.5 / 22	290	2000	2350	10.8
DP40030	400		1.5 / 22	290	3000	3350	14.2