

## FLEXIBLE PACKER WITH BY-PASS

### PRODUCT DESCRIPTION

BurrowTech Flexible Packer with By-pass are products that allow point repair while there is already fluid in the pipes. These are produced by vulcanizing SBR+NR rubber and high-strength fabrics. It is resistant to temperatures between -30°C and +70°C. The biggest advantage is when evacuating inside the pipe, thanks to its wheeled and by-pass designs. It allows point repair and rapid access to the patch area to be repaired at the same time.

\*Can be produced as a Push Rod compatible head.



Wheel and By-pass System



Patch Length Stripes

## FLEXIBLE PACKER WITH BY-PASS

Product Code	Size Usage Range		Max. Working Pressure	Deflated Plug Dimensions			By-Pass Size	Approx. Weight
	Min. Diameter	Max. Diameter		Diameter	Length	Total Length		
	mm	mm	bar / psi	mm	mm	mm	inch	kg
BTB10015010	100	150	2.5 / 36	68	1000	1350	NA	3.5
BTB10015015	100	150	2.5 / 36	68	1500	18550	NA	4.0
BTB10015020	100	150	2.5 / 36	68	2000	2350	NA	4.5
BTB10015025	100	150	2.5 / 36	68	2500	2850	NA	5.0
BTB10015030	100	150	2.5 / 36	68	3000	3350	NA	5.5
BTB10015040	100	150	2.5 / 36	68	4000	4350	NA	6.0
BTB10015050	100	150	2.5 / 36	68	5000	5350	NA	7.0
BTB15025010	150	250	2.5 / 36	112	1000	1350	2"	8.3
BTB15025015	150	250	2.5 / 36	112	1500	18550	2"	9.4
BTB15025020	150	250	2.5 / 36	112	2000	2350	2"	12.0
BTB15025025	150	250	2.5 / 36	112	2500	2850	2"	17.0
BTB15025030	150	250	2.5 / 36	112	3000	3350	2"	18.0
BTB15025040	150	250	2.5 / 36	112	4000	4350	2"	20.0
BTB15025050	150	250	2.5 / 36	112	5000	5350	2"	23.0
BTB20030010	200	300	2.0 / 29	158	1000	1350	2"	9.5
BTB20030015	200	300	2.0 / 29	158	1500	18550	2"	11.7
BTB20030020	200	300	2.0 / 29	158	2000	2350	2"	13.5
BTB20030030	200	300	2.0 / 29	158	3000	3350	2"	16.0
BTB20030040	200	300	2.0 / 29	158	4000	4350	2"	20.1
BTB20030050	200	300	2.0 / 29	158	5000	5350	2"	24.0
BTB30040010	300	400	1.5 / 22	220	1000	1350	3"	16.0
BTB30040015	300	400	1.5 / 22	220	1500	18550	3"	18.0
BTB30040020	300	400	1.5 / 22	220	2000	2350	3"	22.0
BTB30040030	300	400	1.5 / 22	220	3000	3350	3"	26.0
BTB30040040	300	400	1.5 / 22	220	4000	4350	3"	30.0
BTB30040050	300	400	1.5 / 22	220	5000	5350	3"	34.0
BTB40060015	400	600	1.0 / 15	340	1500	18550	3"	28.0
BTB40060020	400	600	1.0 / 15	340	2000	2350	3"	33.0
BTB40060030	400	600	1.0 / 15	340	3000	3350	3"	41.0
BTB60080015	600	800	1.0 / 15	375	1500	18550	3"	39.0
BTB60080020	600	800	1.0 / 15	375	2000	2350	3"	42.0
BTB60080030	600	800	1.0 / 15	375	3000	3350	3"	48.2
BTB700100015	700	1000	1.0 / 15	584	1500	18550	3"	60.7
BTB700100020	700	1000	1.0 / 15	584	2000	2350	3"	65.4
BTB700100025	700	1000	1.0 / 15	584	2500	2850	3"	70.8
BTB700120020	700	1200	1.0 / 15	584	2000	2350	3"	66.4
BTB700120025	700	1200	1.0 / 15	584	2500	2850	3"	71.8
BTB1000150020	1000	1500	1.0 / 15	860	2000	2350	3"	80.1
BTB1000150030	1000	1500	1.0 / 15	860	3000	3350	3"	96.3