

LATERAL PACKER WITH WHEELS

PRODUCT DESCRIPTION

BurrowTech Lateral Packers with wheels are products that allow point repairs on pipelines. These are produced by vulcanizing SBR+NR rubber and high-strength fabrics. It is resistant to temperatures between -30°C and $+70^{\circ}\text{C}$. The biggest advantage is it move in the pipe easily thanks to wheels design.

*Can be produced as a Push Rod compatible head.



Patch Length Stripes



Wheel System and Connection

LATERAL PACKER WITH WHEELS

Product Code	Size Usage Range		Max. Working Pressure	Deflated Plug Dimensions		
	Min. Diameter	Max. Diameter		Diameter	Length	Total Length
	mm	mm	bar / psi	mm	mm	mm
TB15025010W	150	250	2.5 / 36	102	1000	1170
TB15025015W	150	250	2.5 / 36	102	1500	1670
TB15025020W	150	250	2.5 / 36	102	2000	2170
TB15025030W	150	250	2.5 / 36	102	3000	3170
TB15025040W	150	250	2.5 / 36	102	4000	4170
TB15025050W	150	250	2.5 / 36	102	5000	5170
TB20030010W	200	300	2.0 / 29	150	1000	1170
TB20030015W	200	300	2.0 / 29	150	1500	1670
TB20030020W	200	300	2.0 / 29	150	2000	2170
TB20030030W	200	300	2.0 / 29	150	3000	3170
TB20030040W	200	300	2.0 / 29	150	4000	4170
TB20030050W	200	300	2.0 / 29	150	5000	5170
TB30040010W	300	400	1.0 / 15	220	1000	1170
TB30040015W	300	400	1.0 / 15	220	1500	1670
TB30040020W	300	400	1.0 / 15	220	2000	2170
TB30040030W	300	400	1.0 / 15	220	3000	3170
TB30040040W	300	400	1.0 / 15	220	4000	4170
TB30040050W	300	400	1.0 / 15	220	5000	5170
TB40050015W	400	500	1.0 / 15	293	1500	1670
TB40050020W	400	500	1.0 / 15	293	2000	2170
TB40050030W	400	500	1.0 / 15	293	3000	3170
TB40050040W	400	500	1.0 / 15	293	4000	4170
TB40050050W	400	500	1.0 / 15	293	5000	5170
TB50060015W	500	600	1.0 / 15	340	1500	1670
TB50060020W	500	600	1.0 / 15	340	2000	2170
TB50060030W	500	600	1.0 / 15	340	3000	3170
TB50060040W	500	600	1.0 / 15	340	4000	4170
TB50060050W	500	600	1.0 / 15	340	5000	5170
TB60080015W	600	800	1.0 / 15	375	1500	1670
TB60080020W	600	800	1.0 / 15	375	2000	2170
TB60080030W	600	800	1.0 / 15	375	3000	3170