

LATERAL PACKER

PRODUCT DESCRIPTION

BurrowTech Lateral Packers are products that allow point repairs on pipelines. These are produced by vulcanizing SBR+NR rubber and high-strength fabrics. It is resistant to temperatures between -30°C and +70°C.

*Can be produced as a Push Rod compatible head.



Connection Type



Back Hook Design



Patch Length Stripes



Push Rod Connection



Push Rod Connection

LATERAL PACKER

Product Code	Size Usage Range		Max. Working Pressure	Deflated Plug Dimensions			Approx. Weight
	Min. Diameter	Max. Diameter		Diameter	Length	Total Length	
	mm	mm	bar / psi	mm	mm	mm	kg
TB7010006	70	100	3.0 / 44	43	600	870	0.6
TB7010010	70	100	3.0 / 44	43	1000	1170	0.8
TB7010015	70	100	3.0 / 44	43	1500	1670	1.1
TB7010020	70	100	3.0 / 44	43	2000	2170	1.4
TB7010030	70	100	3.0 / 44	43	3000	3170	2.0
TB7010040	70	100	3.0 / 44	43	4000	4170	2.8
TB7010050	70	100	3.0 / 44	43	5000	5170	3.4
TB8012510	80	125	3.0 / 44	45	1000	1170	1.4
TB8012515	80	125	3.0 / 44	45	1500	1670	2.0
TB8012520	80	125	3.0 / 44	45	2000	2170	2.3
TB8012530	80	125	3.0 / 44	45	3000	3170	4.2
TB8012540	80	125	3.0 / 44	45	4000	4170	5.0
TB8012550	80	125	3.0 / 44	45	5000	5170	5.7
TB10015010	100	150	2.5 / 36	64	1000	1170	1.6
TB10015015	100	150	2.5 / 36	64	1500	1670	2.2
TB10015020	100	150	2.5 / 36	64	2000	2170	2.6
TB10015030	100	150	2.5 / 36	64	3000	3170	4.7
TB10015040	100	150	2.5 / 36	64	4000	4170	5.7
TB10015050	100	150	2.5 / 36	64	5000	5170	6.5
TB15020010	150	200	2.5 / 36	89	1000	1170	1.9
TB15020015	150	200	2.5 / 36	89	1500	1670	2.4
TB15020020	150	200	2.5 / 36	89	2000	2170	2.8
TB15020030	150	200	2.5 / 36	89	3000	3170	3.8
TB15020040	150	200	2.5 / 36	89	4000	4170	4.9
TB15020050	150	200	2.5 / 36	89	5000	5170	5.3
TB15025010	150	250	2.5 / 36	102	1000	1170	2.2
TB15025015	150	250	2.5 / 36	102	1500	1670	2.7
TB15025020	150	250	2.5 / 36	102	2000	2170	3.2
TB15025030	150	250	2.5 / 36	102	3000	3170	4.2
TB15025040	150	250	2.5 / 36	102	4000	4170	5.2
TB15025050	150	250	2.5 / 36	102	5000	5170	6.2