

LONG LATERAL PACKER

PRODUCT DESCRIPTION

BurrowTech Long Lateral Packers are products that allow point repairs on pipelines. These are produced by vulcanizing SBR+NR rubber and high-strength fabrics. It is resistant to temperatures between -30°C and +70°C.

*Can be produced as a Push Rod compatible head.



Connection Type



Back Hook Design



Patch Length Stripes



Push Rod Connection

LONG LATERAL PACKER

Product Code	Size Usage Range		Max. Working Pressure	Deflated Plug Dimensions			Approx. Weight
	Min. Diameter	Max. Diameter		Diameter	Length	Total Length	
	mm	mm	bar / psi	mm	mm	mm	kg
TB20030010	200	300	2.0 / 29	150	1000	1160	3.6
TB20030015	200	300	2.0 / 29	150	1500	1660	4.1
TB20030020	200	300	2.0 / 29	150	2000	2160	5.2
TB20030030	200	300	2.0 / 29	150	3000	3160	11.1
TB20030040	200	300	2.0 / 29	150	4000	4160	8.5
TB20030050	200	300	2.0 / 29	150	5000	5160	10.5
TB30040010	300	400	1.0 / 15	220	1000	1160	11.0
TB30040015	300	400	1.0 / 15	220	1500	1660	11.8
TB30040020	300	400	1.0 / 15	220	2000	2160	14.1
TB30040030	300	400	1.0 / 15	220	3000	3160	18.3
TB30040040	300	400	1.0 / 15	220	4000	4160	22.2
TB30040050	300	400	1.0 / 15	220	5000	5160	25.8
TB40050015	400	500	1.0 / 15	293	1500	1660	23.0
TB40050020	400	500	1.0 / 15	293	2000	2160	25.3
TB40050030	400	500	1.0 / 15	293	3000	3160	29.5
TB40050040	400	500	1.0 / 15	293	4000	4160	33.4
TB40050050	400	500	1.0 / 15	293	5000	5160	37.0
TB50060015	500	600	1.0 / 15	340	1500	1660	25.0
TB50060020	500	600	1.0 / 15	340	2000	2160	29.4
TB50060030	500	600	1.0 / 15	340	3000	3160	31.0
TB50060040	500	600	1.0 / 15	340	4000	4160	33.0
TB50060050	500	600	1.0 / 15	340	5000	5160	37.0
TB60080015	600	800	1.0 / 15	375	1500	1660	33.4
TB60080020	600	800	1.0 / 15	375	2000	2160	44.5
TB60080030	600	800	1.0 / 15	375	3000	3160	50.4
TB700100015	700	1000	1.0 / 15	584	1500	1660	45.0
TB700100020	700	1000	1.0 / 15	584	2000	2160	60.0
TB700100025	700	1000	1.0 / 15	584	2500	2660	75.0
TB700120020	700	1200	1.0 / 15	584	2000	2160	61.0
TB700120025	700	1200	1.0 / 15	584	2500	2660	77.0
TB1000150020	1000	1500	1.0 / 15	860	2000	2160	82.0
TB1000150030	1000	1500	1.0 / 15	860	3000	3160	85.0