



PIC 1.9 LC

Our smallest inspection system – for pipes from DN30. Ideal for inspection of kitchen pipes! Sturdy and robust – and yet portable and easy to handle. With a modern, new control unit in a removable hard case.

LC control unit:

- Intuitive handling of the control unit
- Keypad/high-quality operating buttons and graphic display of the functions
- NEW: Now also with text input!
- Various overlay elements such as meter display (freely configurable activity and positioning)
- Recording (photo/video) to flash drive
- Handy, removable control unit in a sturdy hard case with high-resolution 7" colour monitor
- High-capacity LFP battery
- Handle for transportation and attachment of the control unit

Reel cage:

- Reel cage with 40 m push rod, Ø 4.0 mm
- Push rod guiding plate to prevent rod breakage
- Compatible with other interchangeable cages (PIC 3.0)
- PIC 1.9 axial camera head:
- Stainless steel camera head, Ø 19 mm

PIC 1.9 axial camera head:

- Pressure-resistant up to 2 bar
- From DN30 to DN200
- Navigates pipe bends from DN 30/87°
- Digital module 0.01 lux

PIC 1.9 LCI



Our smallest inspection system – for pipes from DN30. Ideal for inspection of kitchen pipes! Sturdy and robust – and yet portable and easy to handle. With a modern, new control unit in a removable hard case.

LCI control unit:

- Intuitive handling of the control unit
- Keypad/high-quality operating buttons and graphic display of the functions
- NEW: Now also with text input!
- Various overlay elements such as meter display (freely configurable activity and positioning)
- Recording (photo/video) to flash drive
- High-resolution 7" colour monitor directly integrated into the reel frame
- High-capacity LFP battery
- Handle for transporting the reel frame

Reel cage:

- Reel cage with 40 m push rod, Ø 4.5 mm
- Push rod guiding plate to prevent rod breakage
- Compatible with other interchangeable cages (PIC 3.0)

PIC 1.9 axial camera head:

- Stainless steel camera head, Ø 19 mm
- PIC 1.9 protecting sleeve
- Pressure-resistant up to 2 bar
- From DN30 to DN200
- Navigates pipe bends from DN 30/87°
- Digital module 0.01 lux