



## PIC 3.0 LC

Our small inspection system – for pipes from DN40. Perfect for inspecting toilet pipes or for renovation! Sturdy and robust – and yet portable and easy to handle. With a modern, new control unit in a removable hard case.

### LC control unit:

- Intuitive handling of the control unit
- Keypad/high-quality operating buttons and graphic display of the functions
- NEW: Now also with text input!
- Various overlay elements such as meter display (freely configurable activity and positioning)
- Recording (photo/video) to flash drive
- Handy, removable control unit in a sturdy hard case with high-resolution 7" colour monitor
- High-capacity LFP battery
- Handle for transportation and attachment of the control unit

### Reel cage:

- Reel cage with 40 m push rod, Ø 6.0 mm
- Push rod guiding plate to prevent rod breakage
- Compatible with other interchangeable cages (PIC 1.9)

### PIC 3.0 axial camera head:

- Stainless steel camera head, Ø 30 mm
- PIC 3.0 protecting sleeve
- Automatic horizon compensation function
- Pressure-resistant up to 1 bar
- From DN40 to DN200
- Navigates pipe bends from DN 50/87°
- Digital module 0.01 lux

## PIC 3.0 LCI



Our small inspection system – for pipes from DN40. Perfect for inspecting toilet pipes or for renovation! Sturdy and robust – and yet portable and easy to handle. With a modern, new control unit – integrated into the reel frame.

### LCI control unit:

- Intuitive handling of the control unit
- Keypad/high-quality operating buttons and graphic display of the functions
- NEW: Now also with text input!
- Various overlay elements such as meter display (freely configurable activity and positioning)
- Recording (photo/video) to flash drive
- High-resolution 7" colour monitor directly integrated into the reel frame
- High-capacity LFP battery
- Handle for transporting the reel frame

### Reel cage:

- Reel cage with 40 m push rod, Ø 6.0 mm
- Push rod guiding plate to prevent rod breakage
- Compatible with other interchangeable cages (PIC 1.9)

### PIC 1.9 protecting sleeve

- Stainless steel camera head, Ø 30 mm
- PIC 3.0 protecting sleeve
- Automatic horizon compensation function
- Pressure-resistant up to 1 bar
- From DN40 to DN200
- Navigates pipe bends from DN 50/87°
- Digital module 0.01 lux