



PIC 5.5 LC

Our medium-sized inspection system – for pipes from DN70. Perfect for inspecting toilet pipes or for renovation! Sturdy and robust – and yet portable and easy to handle. With a modern, new control unit in a removable hard case – on a mobile stainless steel reel frame.

LC control unit:

- Intuitive handling of the control unit
- Keypad/high-quality operating buttons and graphic display of the functions
- NEW: Now also with text input!
- Various overlay elements such as meter display (freely configurable activity and positioning)
- Recording (photo/video) to flash drive
- Handy, removable control unit in a sturdy hard case with high-resolution 7" colour monitor
- Handle for transportation and attachment of the control unit
- Adjustable reel wheels for easy transport
- Vertically adjustable handle for transportation and attachment of the control unit

Reel cage:

- Reel cage with 70 m push rod, Ø 7.5 mm (optional 100 m)
- Push rod guiding plate to prevent rod breakage
- Compatible with other interchangeable BurrowTech camera heads (PIC 5.5 long and short version, PIC 3.0)
- Compatible with other interchangeable cages (PIC 3.0, PIC 1.9)

PIC 5.5 axial camera head:

- Stainless steel camera head, Ø 55 mm
- PIC 5.5 protecting sleeve
- Automatic horizon compensation function
- Pressure-resistant up to 5 bar
- From DN70 to DN500
- Navigates pipe bends from DN 90/87°
- Digital module 0.01 lux
- High-capacity LFP battery



PIC 5.5 PELI

Our medium-sized inspection system – for pipes from DN70. Perfect for inspecting toilet pipes or for renovation! Sturdy and robust – and yet portable and easy to handle. With a large control unit incl. membrane keypad – in a removable hard case – on a mobile stainless steel reel frame.

PELI control unit:

- Control unit with 10" sunreflect monitor
- Detachable control unit in a rugged PELI case
- Data recording possible
- Display of meter value
- 128 GB internal hard disk storage (extendable)
- Wi-Fi capable (data transmission, updates)
- Keypad
- Video output
- Infinitely variable lighting control
- 220 V/ 50 Hz mains connection
- High-capacity LFP battery (a second battery can also be installed)
- Video recording and image storage
- 2 USB ports
- Pre-installed GEJOScan capture software (can be activated by phone/e-mail)

Reel cage:

- Reel cage with 70 m push rod, Ø 7.5 mm (optional 100 m)
- Push rod guiding plate to prevent rod breakage
- Compatible with other interchangeable BurrowTech camera heads (PIC 5.5 short and long version, PIC 3.0)
- Compatible with other interchangeable cages (PIC 3.0, PIC 1.9)

PIC 5.5 axial camera head:

- Stainless steel camera head, Ø 55 mm
- PIC 5.5 protecting sleeve
- Automatic horizon compensation function
- Pressure-resistant up to 5 bar
- Navigates pipe bends from DN 90/87°
- Digital module 0.01 lux